

Series 6, Built-in fridge with freezer section, 177.5 x 56 cm, soft close flat hinge KIL82ADD0G









Included accessories

3 x egg tray, 1 x ice cube tray, 1 x Heavy-duty hinge support

Optional accessories

KSZGGM00 Butter box

The spacious built-in fridge with extra-large **** freezer compartment, VitaFresh XXL <0°C> system, alarm function and soft closing door for optimal storage.

- VitaFresh XXL Pro near 0°C: climate-controlled compartments lock in freshness and nutrients for longer.
- Individual Temperature Control: separate temperature settings for your fridge and freezer.
- High-stability door trays: more height means more flexible space and stability.
- LED lighting: all your items in perfect view.

A ↑ G

• Super Cool function: cools new food faster, to protect what is already inside.

Technical Data Average annual energy consumption in kilowatt hour per year (kWh/a):142 kWh/annum Sum of volume of chill compartments: 246 l Airborne acoustical noise emissions:34 dB(A) re 1 pW Airborne acoustical noise emission class:B Installation type:Built-in Door panel options: Not possible Width of the appliance:558 mm Min. required niche size for installation (HxWxD): 1775.0 x 560 x 550 Net weight:58.8 kg Fuse protection:10 A Frequency: 50 Hz Length of electrical supply cord:230.0 cm Number of compressors:1 Reversible Door Hinge:Yes Number of Adjustable Shelves in fridge compartment (Stck): 3 Brand: Bosch Product name / Commercial code: KIL82ADD0G Product category: Refrigerator cabinet Frost free system:No Installation type:Integrated Included accessories: ..3 x egg tray, 1 x ice cube tray, 1 x Heavy-duty hinge support





Series 6, Built-in fridge with freezer section, 177.5 x 56 cm, soft close flat hinge KIL82ADD0G

The spacious built-in fridge with extra-large **** freezer compartment, VitaFresh XXL <0°C> system, alarm function and soft closing door for optimal storage.

 Fixed hinge, SoftClosing Door - dampens door movement, for smooth and effortless closure

Performance and Consumption

- EU19_EEK_D: D
- Total Volume : 280 l
- Annual Energy Consumption: 142 kWh/a
- Noise Level: 34 dB, EU19_Noise emission class_D: B

Functions

- Bright interior LED fridge light in fridge section
- Built-in fridge

Design features

- NO_FROST_NEU_BL, never have to defrost ever again
- EU19_Fast freezer facility_D
- Separate, electronic temperature control with LED display
- 1 compressor
- Super Cooling: automatic deactivation
- Optical and accoustical
- Automatic defrost fridge

Design features

- Net Fridge Volume : 246 l
- 6 safety glass shelves in fridge compartment of which 3 are height adjustable
- 5 door bins
- Metal bottle rack

Freshness System

- 1 VitaFresh drawer with humidity control Fruits and vegetables retain vitamins and stay fresh for longer
- 1 MultiBox Transparent drawer with a rippled bottom, ideal for storing fruits and vegetables.

Food freshness system

- Net Freezer Volume : 34 l
- Freezing capacity $24h:2.5\ kg$
- Temperature rise time : EU19_Temperature rise time_D: 18 H
- Ice box
- Ice cube tray
- 1 hinged freezer compartment
- none

Dimension and installation

- Dimensions: 177.2 cm H x 55.8 cm W x 54.8 cm D
- Niche Dimensions: 177.5 cm H x 56 cm W x 55 cm D

Key features - Fridge section

- Right hinged door, door reversible
- Height adjustable front feet
- Length of power cord:230 cm
- Climate Class: SN-ST
- 220 240 V

Key features - Freezer section

- Heavy-duty hinge support, 3 x egg tray, 1 x ice cube tray

Country Specific Options

- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.


Design features


Dimension and installation

Additional features



Series 6, Built-in fridge with freezer section, 177.5 x 56 cm, soft close flat hinge KIL82ADD0G







Maximal permissible weight of the unit fronts

Fitted unit fronts that exceed the permissible weight may cause damage and result in functional impairment of the hinges Δ Weight Δ : Appliance door height including hinges in mm


- B: Undamped hinge, unit front in kg
- C: Damped hinge, unit front in kg
- D: Additional possible load in kg with heavy load kit

	Α	B	С	D
	1500-1750	22	22	
	720-1400	19	19	B+5 / C+5
	A1	15	19	
	Δ2	15	19	






measurements in mm



measurements in mm Recommended gap dimensions for flat hinges



The gap dimensions recommended in the table must be adhered to in order to ensure that appliance doors do not collide with anything when they are opened, and to avoid causing damage to kitchen units.