

N 70, GAS HOB, 75 CM, TEMPERED GLASS, BLACK T27PIQ4S0



Z1365WX0 Wireless food thermometer
Z2402X0 Small pot support
Z2471X0 Wok ring
Z2480X0 Simmer plate
Z9404SE0 4 pieces Set
Z9406SE0 6 pieces Set

The gas hob with precise flame control, removable dials and semi-continuous pan supports that are suitable for dishwashers for Comfort Clean.

- $\sqrt{\text{FlameSelect}^{\text{@}}}$: Gain precise control of your flame.
- $\sqrt{\,}$ Metallic Sword Dial: Precise and removable for easy cleaning.
- $\sqrt{}$ Cast Iron Pan Supports: Maximum stability, easy handling, and dishwasher cleaning.
- $\sqrt{}$ Wok Burner: Powerful cooking at up to 4 kW.
- $\sqrt{\ }$ Gas Safety Cut-Off: Safety first! No flame, no gas flow.

gas hob w
Built-in
Gas
5
45 x 560-562 x
752 mm
54x752x520 mm
145 x 793 x 597 mm
19.3 kg
21.9 kg
without
Front
Tempered glass
Black
Black
100.0 cm
4242004284659
11500 W
3 A
220-240 V
50; 60 Hz



N 70, GAS HOB, 75 CM, TEMPERED GLASS, BLACK T27PIQ4S0

Design

- tempered glass surface, black
- Two built-in options:
- - Flush installation Surface mounted installation: install the hob either flush or slightly raised on the worktop
- Cast iron pan supports with rubber feet

Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels
- Design co-ordinated control dials, front: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 burner hob
- Left front: Economy burner up to 1 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: Wok burner up to 4 KW (depending on gas type)
- Right rear: High speed burner up to 3 KW (depending on gas type)
- Right front: Standard burner up to 1.75 KW (depending on gas type)

Cleaning

- Removable control dials for easy cleaning between knobs.
- Dishwasher suitable pan supports for easy cleaning.
- Cast iron pan supports with rubber feet: little weight and compact form, yet high stability due to continuous surface.

Safety

• Flame failure safety device: prevents unwanted gas flow when flame

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- \bullet Dimensions of the product (HxWxD mm): 54 x 752 x 520
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 492)
- Min. worktop thickness: 30 mm
- \bullet If installed flush, minimum worktop thickness is 30mm.
- Power cord: 1 m
- Connected load: 11.5 KW



N 70, GAS HOB, 75 CM, TEMPERED GLASS, BLACK T27PIQ4S0

